

ULTRAVIOLET LIGHT – AQUAFINE VL SERIES

FEATURES & SPECIFICATIONS

		Model	
		VL 200	VL 410
General	Disinfection 94% UVT GPM (m3/hr)	11 (2.5)	18 (4.1)
	Disinfection 99% UVT GPM (m3/hr)	12 (2.7)	20 (4.5)
	Amount of Lamps (LPHO)	1	1
	Lamp Operating Power (watt)	25	46
	Total Operating Power (watt)	35	60
UV Chamber	Chamber Material	Type 316L Stainless Steel	Type 316L Stainless Steel
	Dimension	15 ' x 3.5 ' (45 cm x 8.9 cm)	23.5 ' x 3.5 ' (60 cm x 8.9 cm)
	Interior Surface Finish	R32	R32
	Inlet / Outlet Flange Size	1 ' (25 mm)	1.5 ' (37 mm)
	Inlet / Outlet Configuration	S - Shape	S - Shape
	IP Rating	33	33
Controller	Lamp Replacement Countdown in Days	-	Yes
	Audible Lamp Replacement / Fault Alarm	-	Yes
	Audible Low UVI Alarm	-	Yes (Sensor Only)
	AUX Output (Lamp Out Alert)	-	Yes
	Dimension - Monitored (H x W x D)	-	8.8 ' x 3.2 ' x 2.5 ' (22.3 cm x 8.1 cm x 6.4 cm)
	Dimension - Non-Monitored (H x W x D)	-	6.8 ' x 3.2 ' x 2.5 ' (17.2 cm x 8.1 cm x 6.4 cm)
	IP Rating	-	54